



## A2F50S-PK

**Term Tech ATEX Non-Armoured Brass Gland  
Pack M50 Thread 31.5mm-37mmØ Range  
Includes Accessories (Pack of 1)**



The Termination Technology range of A2F Brass cable glands are suitable for use with all types of unarmoured cable. ATEX 130325X rated to provide additional protection in hazardous areas. Supplied in complete packs with gland, locknut and PVC shroud and seals, offering an IP66 rating (IP68 when installed with an IP Washer) Sizes up to and including M32 come as packs of 2, M40 and above as packs of 1.



**Termination  
Technology Ltd**

*Quality and Service*

The company with the **RIGHT** connections at the **RIGHT** price.

Company Registration Number: 05062297


**W:** [www.termtech.co.uk](http://www.termtech.co.uk)

**T:** 01179 354 900

**E:** [sales@termtech.co.uk](mailto:sales@termtech.co.uk)

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,  
Bristol BS5 7UW





## Technical Data

### Colour and Material

Material	Brass
----------	-------

### Application Type, Size and Range

Cable Ø Range (mm)	31.5-37
Environmental Application	Zone 1, Zone 2, Zone 21 & Zone 22
IP Rating	IP67
Suitable Cable Type	Non Armoured

### Dimensions

Dimension A (mm)	31.5-37
Dimension D (mm)	22
Dimension E (mm)	45
Dimension N (mm)	M50 X 1.5
Gland Body Hex Details A/C (mm)	63.3
Gland Body Hex Details A/F (mm)	57
Nut Hex Details A/C (mm)	61
Nut Hex Details A/F (mm)	55
Thread Size	M50

### Product Specification

Specification	EN 60079-0:2009, IEC 60079-0:2011, EN 60079-1:2007 & EN60079-7:2007
Specific Approvals	ITS11ATEX17453X for Ex d & Ex e

### Temperature and Fire Information

Continuous Operating Temperature (°C)	-20 to +100
---------------------------------------	-------------

