Datasheet



ADL19

Term Tech Adhesive Lined Heatshrink Tubing 3:1 Shrink Ratio 19.1mmØ Black 1200mm Length



The Termination Technology range of Adhesive Line Heatshrink is manufactured from Crosslinked Polyolefin to be robust in a range of environments. Supplied in sturdy 1200mm lengths with an inner adhesive that bonds to a wide range of materials. With a high shrink ratio of 3:1 each size can be utilised more effectively to cover a larger range of applications, effectively making the product more efficient and reducing waste. Medium walled adhesive lined Heatshrink is also available for more heavy duty applications.



The company with the RIGHT connections at the RIGHT price.

ping data first





W: www.termtech.co.uk T: 01179 354 900

E: sales@termtech.co.uk

Datasheet



Technical Data

Colour and Material

Material Crosslinked Polyolefin

Colour Black

Dimensions

Product Length (mm) 1200

Durability

Fungus Resistance No Growth ASTM G-21

Electrical Ratings

Dielectric Strength (kV/mm) 22

Volume Resistivity (Ohm/cm) 10 ^14

Physical Attributes

Adhesive Lined

Flexible Flexibility

15 Tensile Strength (Mpa) 400

Maximum Elongation (%)

Specific Gravity (g/cm³) 1.25 ASTM D-792, ISO R1183

Yes

Water Absorption (%) 0.15 VDE 0472

Temperature and Fire Information

Continuous Operating Temperature (°C) -55 to +110

Shrink Temperature (°C) +95

Fire Rating Flame Retardant

Flammability Testing **ASTM D-876**



W: www.termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Company Registration Number: 05062297








Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,

T: 01179 354 900 E: sales@termtech.co.uk

Bristol BS5 7UW

Datasheet







The company with the RIGHT connections at the RIGHT price.

Epim





W: www.termtech.co.uk T: 01179 354 900

E: sales@termtech.co.uk