# **Datasheet**



### **BIMET185M12**

Term Tech Bi-Metallic Tube Terminal
Aluminium Barrel Copper Palm 185mm<sup>2</sup> Cable
12mm Hole



The Termination Technology range of Bi-Metal lugs are suitable for terminating cables with aluminium conductors onto copper busbars without the risk of electrolytic corrosion and ensuring longevity. Supplied with a greased internal barrel and capped to prevent leakage. We would recommend using an indent crimper as aluminium is a softer metal than copper and the wall thickness of the lug is thicker to compensate.



The company with the RIGHT connections at the RIGHT price.

**Epim** 





W: www.termtech.co.uk
T: 01179 354 900
E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW

# **Datasheet**



### **Technical Data**

#### **Colour and Material**

**Body Material Aluminum Head Material Electrolytic Copper** 

#### **Application Type, Size and Range**


Cable Size (mm<sup>2</sup>) 185

#### **Dimensions**

Dimension d1 (mm) 18.5 Dimension d2 (mm) 13 Dimension d4 (mm) 32 Dimension L (mm) 122 Fixing Hole (mm) 12

#### **Product Specification**

DIN 48201/DIN46329 Specification





Company Registration Number: 05062297

W: www.termtech.co.uk T: 01179 354 900 E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,

**Bristol BS5 7UW** 

The company with the RIGHT connections at the RIGHT price.





