



BIMET25M12

Term Tech Bi-Metallic Tube Terminal Aluminium Barrel Copper Palm 25mm² Cable 12mm Hole



The Termination Technology range of Bi-Metal lugs are suitable for terminating cables with aluminium conductors onto copper busbars without the risk of electrolytic corrosion and ensuring longevity. Supplied with a greased internal barrel and capped to prevent leakage. We would recommend using an indent crimper as aluminium is a softer metal than copper and the wall thickness of the lug is thicker to compensate.



**Termination
Technology Ltd**

Quality and Service

The company with the RIGHT connections at the RIGHT price.

Company Registration Number: 05062297

W: www.termtech.co.uk

T: 01179 354 900

E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,
Bristol BS5 7UW





Technical Data

Colour and Material

Body Material	Aluminum
Head Material	Electrolytic Copper

Application Type, Size and Range

Cable Size (mm ²)	25
-------------------------------	----

Dimensions

Dimension d1 (mm)	7
Dimension d2 (mm)	13
Dimension d4 (mm)	16
Dimension L (mm)	90
Fixing Hole (mm)	12

Product Specification

Specification	DIN 48201/DIN46329
---------------	--------------------

