Datasheet



BIMET35M12

Term Tech Bi-Metallic Tube Terminal Aluminium Barrel Copper Palm 35mm² Cable 12mm Hole



The Termination Technology range of Bi-Metal lugs are suitable for terminating cables with aluminium conductors onto copper busbars without the risk of electrolytic corrosion and ensuring longevity. Supplied with a greased internal barrel and capped to prevent leakage. We would recommend using an indent crimper as aluminium is a softer metal than copper and the wall thickness of the lug is thicker to compensate.



Company Registration Number: 05062297

T: 01179 354 900 E: sales@termtech.co.uk

W: www.termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, **Bristol BS5 7UW**









Datasheet



Technical Data

Colour and Material

Body Material Aluminum

Head Material Electrolytic Copper

Application Type, Size and Range

Cable Size (mm²) 35

Dimensions

 Dimension d1 (mm)
 8.5

 Dimension d2 (mm)
 13


 Dimension d4 (mm)
 16

 Dimension L (mm)
 90

 Fixing Hole (mm)
 12

Product Specification

Specification DIN 48201/DIN46329





W: www.termtech.co.uk
T: 01179 354 900
E: sales@termtech.co.uk

Bristol BS5 7UW

The company with the RIGHT connections at the RIGHT price.

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,





