Datasheet



BIMET50M12

Term Tech Bi-Metallic Tube Terminal
Aluminium Barrel Copper Palm 50mm² Cable
12mm Hole



The Termination Technology range of Bi-Metal lugs are suitable for terminating cables with aluminium conductors onto copper busbars without the risk of electrolytic corrosion and ensuring longevity. Supplied with a greased internal barrel and capped to prevent leakage. We would recommend using an indent crimper as aluminium is a softer metal than copper and the wall thickness of the lug is thicker to compensate.



T: 01179 354 900 E: sales@termtech.co.uk

W: www.termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW







Datasheet



Technical Data

Colour and Material

Body Material Aluminum

Head Material Electrolytic Copper

Application Type, Size and Range

Cable Size (mm²) 50

Dimensions

 Dimension d1 (mm)
 9.6

 Dimension d2 (mm)
 13


 Dimension d4 (mm)
 20

 Dimension L (mm)
 90

 Fixing Hole (mm)
 12

Product Specification

Specification DIN 48201/DIN46329





W: www.termtech.co.uk
T: 01179 354 900
E: sales@termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW





