Datasheet



BUR32-HT

Term Tech Un-Insulated Terminals Ring 1.5mm²-2.5mm² Cable High Temperature 3.2mm Hole (Bag of 100)



The Termination Technology range of uninsulated terminals are manufactured from copper sheet, allowing for larger hole size to conductor size comparatively. Perfect for use in higher temperature applications where insulated terminals would not be suitable. Standard terminals are tin plated, suitable up to +75°C. High temperature versions are Nickel plated, suitable up to +250°C.



The company with the RIGHT connections at the RIGHT price.

Company Registration Number: 05062297







W: www.termtech.co.uk T: 01179 354 900 E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW



Technical Data

Colour and Material	
Material	Copper
Plating Material	Nickel
Application Type, Size and Range	
Cable Size Range (mm ²)	1.5 - 2.5
Number of Cables Accepted	1
Suitable Cable Type	Copper Cores
Dimensions	
Ring Size (mm)	3.2
Product Specification	
Specification	BS EN 61238-1 2003 & IEC 61238-2003
Quantities and Packaging	
Packaging	Euroslot trade counter pack
Product Count	100
Temperature and Fire Information	
Max Operating Temperature (°C)	250



The company with the RIGHT connections at the RIGHT price.

Company Registration Number: 05062297







W: www.termtech.co.uk T: 01179 354 900 E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW