


HS3.2-25KIT

Term Tech Heatshrink Kit Box 3.2mm-25mmØ Cut Lengths Various Colours



The Termination Technology Heatshrink kit box is supplied with a range of colours and sizes to provide an easy to transport selection to cover common applications. Supplied in an easy to transport carry case with a clear lid and handle. Each size is included with all phase colours and clear in cut lengths with a 2:1 shrink ratio.



**Termination
Technology Ltd**

Quality and Service

The company with the **RIGHT** connections at the **RIGHT** price.

Company Registration Number: 05062297


W: www.termtech.co.uk

T: 01179 354 900

E: sales@termtech.co.uk

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,
Bristol BS5 7UW





Technical Data

Dimensions

Product Height (mm)	55
Product Length (mm)	370
Product Width (mm)	260

Durability

Chemical Resistance	Resistant to common fluids and solvents
Fungus Resistance	Tested with no growth occurring

Electrical Ratings


Dielectric Strength (kV/mm)	Min 19.7 Tested to ASTM D-2671
Volume Resistivity (Ohm/cm)	Min 10 ¹³ Tested to ASTM D-876


Kit Details

Kit Components	5x HS3.2BLK (170mm length) 5x HS3.2BROWN (170mm length) 5x HS3.2BLUE (170mm length) 5x HS3.2GREY (170mm length) 5x HS3.2G/Y (170mm length) 2x HS3.2CLEAR (170mm length) 5x HS4.8BLK (170mm length) 5x HS4.8BROWN (170mm length) 5x HS4.8BLUE (170mm length) 5x HS4.8GREY (170mm length) 5x HS4.8G/Y (170mm length) 2x HS4.8CLEAR (170mm length) 5x HS6.4BLK (170mm length) 5x HS6.4BROWN (170mm length) 5x HS6.4BLUE (170mm length) 5x HS6.4GREY (170mm length) 5x HS6.4G/Y (170mm length) 2x HS6.4CLEAR (170mm length) 5x HS9.5BLK (170mm length) 5x HS9.5BROWN (170mm length) 5x HS9.5BLUE (170mm length) 5x HS9.5GREY (170mm length) 5x HS9.5G/Y (170mm length) 2x HS9.5CLEAR (170mm length) 5x HS12.7BLK (170mm length) 5x HS12.7BROWN (170mm length) 5x HS12.7BLUE (170mm length) 5x HS12.7GREY (170mm length) 5x HS12.7G/Y (170mm length) 2x HS12.7CLEAR (170mm length) 5x HS19BLK (170mm length) 5x HS19BROWN (170mm length) 5x HS19BLUE (170mm length) 5x HS19GREY (170mm length) 5x HS19G/Y (170mm length) 2x HS19CLEAR (170mm length) 5x HS25BLK (170mm length) 5x HS25BROWN (170mm length) 5x HS25BLUE (170mm length) 5x HS25GREY (170mm length) 5x HS25G/Y (170mm length) 2x HS25CLEAR (170mm length) 1x A46KITBOX
----------------	--

Physical Attributes

Adhesive Lined	No
----------------	----





Product Specification

CE Compliant	Yes
RoHS Compliant	Yes

Temperature and Fire Information

Continuous Operating Temperature (°C)	-55 to +135
Shrink Temperature (°C)	+90 to Start Shrinking
Fire Rating	UL224 VW-1; MIL-I-23053/5 Class 1 & 3



HS25 Phase Colours	Clear Heatshrink all sizes.
HS12.7 Phase Colours	HS19 Phase Colours
HS9.5 Phase Colours	HS6.4 Phase Colours
HS3.2 Phase Colours	HS4.8 Phase Colours

