



## HSB2.4BROWN

**Term Tech Heatshrink Box 2:1 Ratio 2.4mmØ  
Expanded, 1.2mmØ Recovered Brown (15m  
Box)**



The Termination Technology range of thin wall Cross linked Polyolefin Heatshrink is designed for commercial use with common uses including insulation, wire bundling, colour coding and mechanical protection. Available in a range of colours and sizes, supplied in a dispensable box.



**Termination  
Technology Ltd**

*Quality and Service*

The company with the **RIGHT** connections at the **RIGHT** price.

Company Registration Number: 05062297


**W:** [www.termtech.co.uk](http://www.termtech.co.uk)

**T:** 01179 354 900

**E:** [sales@termtech.co.uk](mailto:sales@termtech.co.uk)

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,  
Bristol BS5 7UW





## Technical Data

### Colour and Material

|          |                        |
|----------|------------------------|
| Material | Crosslinked Polyolefin |
| Colour   | Brown                  |

### Durability

|                     |                                         |
|---------------------|-----------------------------------------|
| Chemical Resistance | Resistant to common fluids and solvents |
| Fungus Resistance   | Tested with no growth occurring         |

### Electrical Ratings

|                             |                                    |
|-----------------------------|------------------------------------|
| Dielectric Strength (kV/mm) | Min 19.7 Tested to ASTM D-2671     |
| Volume Resistivity (Ohm/cm) | Min $10^{13}$ Tested to ASTM D-876 |

### Physical Attributes

|                |    |
|----------------|----|
| Adhesive Lined | No |
|----------------|----|

### Product Specification

|                |     |
|----------------|-----|
| CE Compliant   | Yes |
| ROHS Compliant | Yes |

### Quantities and Packaging

|           |                           |
|-----------|---------------------------|
| Packaging | Cardboard Dispensable Box |
|-----------|---------------------------|

### Temperature and Fire Information

|                                       |                                       |
|---------------------------------------|---------------------------------------|
| Continuous Operating Temperature (°C) | -55 to +135                           |
| Shrink Temperature (°C)               | +90 to Start Shrinking                |
| Fire Rating                           | UL224 VW-1; MIL-I-23053/5 Class 1 & 3 |





**Termination  
Technology Ltd**

*Quality and Service*

The company with the **RIGHT** connections at the **RIGHT** price.

Company Registration Number: 05062297

**W:** [www.termtech.co.uk](http://www.termtech.co.uk)

**T:** 01179 354 900

**E:** [sales@termtech.co.uk](mailto:sales@termtech.co.uk)

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,  
Bristol BS5 7UW

