


## RGM4L1.5

### Term Tech MICC Brass Glands 20mm Light Duty 4L1.5 (Pack of 10)



The Termination Technology range of MICC accessories include pots & seals, glands and shrouds. Alongside our metal fixing clips they offer everything you would need for the installation of mineral insulated cables. A range of MICC tooling is also available from stock including crimpers, potting tools, ringing tools and more.



**Termination  
Technology Ltd**

*Quality and Service*

The company with the **RIGHT** connections at the **RIGHT** price.

Company Registration Number: 05062297

**W:** [www.termtech.co.uk](http://www.termtech.co.uk)

**T:** 01179 354 900

**E:** [sales@termtech.co.uk](mailto:sales@termtech.co.uk)

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road,  
Bristol BS5 7UW





## Technical Data

### Colour and Material

Material	Brass
----------	-------

### Application Type, Size and Range

Environmental Application	ATEX approved for Zone 1, Zone 2, Zone 21 and Zone 22 hazardous areas
---------------------------	---

IP Rating	IP54
-----------	------

Number of Cables Accepted	1
---------------------------	---

Suitable Cable Type	4L1.5 Mineral Insulated Cable (MICC)
---------------------	--------------------------------------

### Dimensions

Approx Assembled Length (mm)	22
------------------------------	----

Gland Body Hex Details A/C (mm)	24.4
---------------------------------	------

Gland Body Hex Details A/F (mm)	22
---------------------------------	----

Nut Hex Details A/C (mm)	21.2
--------------------------	------

Nut Hex Details A/F (mm)	19
--------------------------	----

Thread Length (mm)	11
--------------------	----

Thread Size	M20
-------------	-----

### Product Specification

Specification	EN60079-0:2009, IEC60079-0:2011, EN60079-1:2007, EN60079-7:2007
---------------	---

Specific Approvals	ITS11ATEX17453X Certification
--------------------	-------------------------------

### Quantities and Packaging

Product Count	10
---------------	----

### Temperature and Fire Information

Continuous Operating Temperature (°C)	-20 to +100
---------------------------------------	-------------

